Powys County Council

Dep	Departure from Standards DP121				
Submission Form					
1.0	Basic Details				
1.1	Developer / Client	Welsh Government			
1.2	Planning Application No.				
1.3	Scheme Name	A483/A489 Newtown Bypass			
1.4	Road / Location / Grid Reference	Wern Ddu Lane			
1.5	Design Organisation	Atkins (Swansea) as designer to Alun Griffiths Contractors Ltd			
2.0	Overall Justification				
2.1	Design Speed and method of assessment	50A kph TD9/93 – Highway Link Design (Para 1.7) Calculated Ac and Lc values fall well below the values in Figure 1 and we have therefore interpolated the design speed.			
2.2	Speed limit	Derestricted			
2.3	Options / Alternatives Rejected (constraints)	 Options were constrained by the following considerations:- Alignment of the existing road. Alignment of the bypass and suitable crossing point where the bypass is in cutting. The location of the existing high pressure gas main. Diversion of this apparatus would be extremely costly and introduce additional programming constraints. 			
2.4	Relevant Standard	TD 9/93 Highway Link Design			
2.5	Relevant Clause	Clause 3.12 – Radii less than 90m			
2.6	Existing Departures at the site	Unknown but likely to be similar in nature to those applied for in this submission.			
2.7	Full Details of Proposed Departure	The proposed Horizontal Alignment at Wern Ddu Lane does not comply with TD9/93 Clause 3.12. TD9/93 Clause 3.12 states that 'radii less than 90m on the mainline are Departures from standard.' The Table below outlines details of the proposed and compliant horizontal curvature for the departure, along with the corresponding constraints.			

		Radii Proposed Horizontal Radius = 45m (Ch 0 to 21m) Horizontal Radius = 60m (Ch 162 to 200m) Horizontal Radius = 50m (Ch 253 to 287m) Compliant	Constraints Existing road and bypalignment and existing pressure gas main.	
2.8	Associated Departures &	Horizontal Radius = 90m DP119 – Wern Ddu Lane –	•	
	Relaxations	DP120 – Wern Ddu Lane – R = 120m and 100m (2 Step	_	
3.0	Other Information		,	
3.1	Non-motorised users considerations (eg Active Travel (Wales) Act)	Existing connectivity for non-motorised users will be maintained by the re-provision/diversion of any public rights of way bisected by the proposed scheme.		
3.2	Street Lighting provision: Existing and Proposed	There is no existing street lighting at this location. No street lighting is proposed at this location.		
3.3	Other relevant technical information such as vehicle restraint systems, proximity to junctions etc.	None		
3.4		n associated with the depart	ure.	Supplied (Y/N)
	 Location plan typically at 1:10000 showing the scheme extent and existing/associated departures. 		Y	
		ding road markings typically	1:2500 for links and	Υ
		Checks where relevant includ	ling design year	Υ
	 Visibility Graphs fo 	r SSD departures.		N

	 Risk Assessment associated with the proposed departure when compared with a fully compliant design (including a designer's risk assessment) 		N Y Y
4.0	Summary		
4.1	Summary of mitigation measures proposed as part of the design solution	The existing alignment of Wern-Ddu Lane combin the narrow carriageway and verge widths result in traffic speeds. The alignment has been designed to a degree of consistency with the existing layout a therefore anticipated that vehicle speeds will be I 2 No. passing bays to be provided either side of the proposed bridge with passing bay signs to discour parking.	n low to maintain nd it is ow.
4.2	Overall Justification. Summarise how the benefits of the proposal outweigh the disbenefits when compared with a fully compliant design.	The net benefit is derived from savings in cost, as reduced environmental impact when compared to compliant design. This alignment was selected to minimise earthwo the associated environmental impact of the route also eliminate the need to divert an existing Wale West Utilities high pressure gas main whilst main degree of consistency to the contiguous sections of this length of new highway and minimising the angle of the proposed bridge. The provision of an alignment that would achieve standard horizontal alignment curves in this locat result in the need to increase earthworks and assenvironmental/landscape impacts. Additionally, the would impact upon the existing high pressure gas increase the skew angle of the proposed bridge.	rks and the lit will the sand taining a teither side skew the tion would ociated he route
5.0	Declarations		
5.1	Name of Designer Proposing Departure Submission.	N.J.R Bebb	
5.2	Title of Designer Proposing Departure Submission.	Divisional Director	

5.3	Declaration of Designer Proposing Departure Submission.	I confirm that in completing the attached departure submission I have used reasonable professional skill and care. I hereby recommend approval of the attached departure from standard submission Signed:
5.4	Declaration of Welsh Government - Overseeing Organisation	Date: 27 th March 2015 Additional Comments from Welsh Government: Name: Signed: Date:
5.5	Powys County Council Comments	Additional Comments from Powys County Council: Name: Date:
5.6	Declaration of Powys County Council - Departure Owner.	I hereby recommend approval of the attached departure from standard submission Name: Position/Responsibility: Signed: Date:
6.0	Departure Endorsement	
6.1	Endorsement of Head of Service	Comments: Name: Signed: Date:

7.0	Technical Review Panel Recommendations	
7.1	Recommendations of Infrastructure Delivery Project Director	Recommendations:
		Name:
		Signed:
		Date:
7.2	Recommendations of Network Management Delivery Team Leader	Recommendations:
		Name:
		Signed:
		Date:
7.3	Recommendations of Standards, DC & Streetworks Team	Recommendations:
	Leader (Chair)	Name:
		Signed:
		Date:
7.4	Endorsement of Deputy Director (Infrastructure Delivery) or Head of Asset Management &	Comments:
	Standards (Network Management)	Name:
	anagement/	Signed:
		Date: